



Cosmos Lac AE

1 Pindou str.
 17672 Kallithea, Athens, Greece.
 Tel.: +30 2109570222 -
 Fax: +30 2109566671
 factory@cosmoslac.com
 www.cosmoslac.com

Technical Data Sheet

PRODUCT	COSMOS LAC PORCELAIN SPRAY N401
DESCRIPTION/ USES	High quality acrylic paint suitable for repair old white bathroom fixtures and make them look like new. Easy to use with high durability ideal for all applications. Perfect for tubs, wash basins refinishing bathtubs, sinks, toilets, shower stalls etc.
Viscosity	18-25 sec (Flow Cup DIN4, 20°C)
Density	0.6-0.8 g/L (Density Cup 100cm ³ /20°C, ASTM D – 1475)
Solids w/w	15-20%
VOC content	650 g/L
Flash Point	-104 °C (based on propellant)
Color	White
Drying time	Touch (20°C, Humidity<65%): 5-10min Through dry (20°C, Humidity <65%) : 1h Maximum hardness: 24 hours
Coverage	5m ² /L
Gloss	90 GLOSS UNIT [GLOSS METER 600ASTM D – 1471]
Film thickness	200µm (wet), 40-45µm (dry)
Can Pressure	4bar (20°C), 8 bar (50°C)
Contents	400ml
Application	Remove all dust, rust, and oil from the surface. Protect the area which you don't want to be painted. Shake the can thoroughly and spray at a distance of 25 - 30cm from the surface. Try the spray on testing surface. For better results apply 2-3 thin coats, 3-5 min apart. Longevity and adhesion will be extended by allowing the new coating to cure for 48h before putting back into use in a wet or humid environment. Best application temperature: 10°C - 25°C
After use	Spray holding the can inverted for 3". Clean the caps with solvent.
Storage	5-35°C. Do not put in vehicles.

ISSUED 27 November 2017, factory@cosmoslac.com