



## DESCRIPTION

Quick-drying synthetic primer for metals, suitable for application on metal surfaces before the final color. It protects against rust and enhances the adhesion of the final color. It has excellent coverage and can be painted over with alkyd or acrylic paint.

## PROPERTIES

- Viscosity: 18-25sec (Flow Cup DIN4, 20°C)
- Density: 0.6-0.8 g/L (Density Cup 100cm<sup>3</sup>/20°C, ASTM D – 1475)
- VOC content: 665 g/L
- Flash Point: -104°C (based on propellant)
- Drying time
  - Touch (20°C, Humidity<65%): 10-15 min
  - Through dry (20°C, Humidity <65%): 1h
  - Maximum hardness: 24h
- Coverage: 2m<sup>2</sup>/400 ml
- Gloss: 1-3 GLOSS UNITS/MATT  
(GLOSS METER 60°ASTM D – 1471)
- Contents: 400 ml

## INSTRUCTIONS FOR USE

### APPLICATION

Remove all dust, rust and oil from the surface. Protect the area which you don't want to be painted. Shake the can thoroughly and spray at a distance of 25-30cm from the surface. Try the spray on testing surface. Apply the primer in several thin layers. For better results apply 2-3 thin coats, 3-5 min apart. **Best application temperature: 10-25°C.**

### AFTER USE

Spray holding the can inverted for 3". Clean the caps with solvent.

### STORAGE

Store between 5-35°C. Do not store in vehicles.

## CAP SYSTEM



### SMART CAP

- Less overspray
- Extreme Coverage
- Fast drying
- Hard chisel lines
- Even coating
- Suitably for effects
- Dual way spraying

## SAFETY

Request SDS


\*Cap indicates the color of the paint

## COLOR RANGE

344 OXIDE RED



345 WHITE



346 GREY



348 BLACK

